

Package: pm3 (via r-universe)

October 29, 2026

Type Package

Title Propensity Score Matching for Unordered 3-Group Data

Version 0.2.0

Maintainer Qiang LIU <dege857@163.com>

Description You can use this program for 3 sets of categorical data for propensity score matching. Assume that the data has 3 different categorical variables. You can use it to perform propensity matching of baseline indicator groupings. The matching will make the differences in the baseline data smaller. This method was described by Alvaro Fuentes (2022) <[doi:10.1080/00273171.2021.1925521](https://doi.org/10.1080/00273171.2021.1925521)>.

License GPL-3

Depends R (>= 4.2.0)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.1

Imports tableone

NeedsCompilation no

Author Qiang LIU [aut, cre]

Config/pak/sysreqs make libicu-dev libx11-dev zlib1g-dev

Repository <https://dege857.r-universe.dev>

Date/Publication 2024-07-23 02:45:38 UTC

RemoteUrl <https://github.com/cran/pm3>

RemoteRef HEAD

RemoteSha 2d9286f6e3610c740278e56a84d3364ed9340c7c

Contents

datatch	2
pm3	2

pm3datalist	3
pm3fit	4
prematurity	4

Index	5
--------------	----------

datach	<i>datach</i>
--------	---------------

Description

Generate new data and define the data.

Usage

datach(data, x)

Arguments

- | | |
|------|--|
| data | A data entry is required. |
| x | The 3 categorical variables that you make matches for. |

Value

A list with data.

pm3	<i>pm3</i>
-----	------------

Description

Propensity score matching for unordered 3-group data

Arguments

- | | |
|--------|---|
| data | need a dataframe |
| x | Enter the 3 categorical variables to be matched.If x is a number, it must be of type 1,2,3. |
| y | Enter the outcome variable for your study. |
| covs | Covariates. Usually the other fitted variables of the model.This is also usually the baseline variable you need to match. |
| factor | Define the categorical variables in your data. |
| CALIP | The number used to match. Usually you don't need to change it. The default is 0.5. |

Details

You can use this program for 3 sets of categorical data for propensity score matching. Assume that the data has 3 different categorical variables. You can use it to perform propensity matching of baseline indicator groupings. The matching will make the differences in the baseline data smaller.

Value

A list with data.

Examples

```
bc<-prematurity
#####Generate data lists and extract data
g<-pm3(data=bc,x="race",y="low",covs=c("age","lwt","ptl"),
factor=c("ui","low","smoke"))
mbc<-g[["mbc"]]
####Compare before and after matching
library(tableone)
allVars <-c("age", "lwt", "ptl")
fvars<-c("ht")
tab2 <- CreateTableOne(vars = allVars, strata = "race" ,
data = bc, factorVars=fvars,addOverall = TRUE )
print(tab2,smd = TRUE)
tab1 <- CreateTableOne(vars = allVars, strata = "race" ,
data = mbc, factorVars=fvars,addOverall = TRUE )
print(tab1,smd = TRUE)
```

pm3datalist

pm3datalist

Description

Identification and formatting of data.

Usage

```
pm3datalist(data, x, y, covs, factor = NULL)
```

Arguments

data	A data entry is required.
x	The 3 categorical variables that you make matches for.
y	Your result variable.
covs	Enter the relevant covariates.
factor	Define categorical variables.

Value

A data.

pm3fit

pm3fit

Description

Generate propensity scores and generate the data to be matched.

Arguments

data	A data entry is required.
x	The 3 categorical variables that you make matches for.
y	Your result variable.
covs	Enter the relevant covariates.
factor	Define categorical variables.

Value

A list with data.

prematurity

A data on indicators for premature newborns.

Description

A data on indicators for premature newborns.

Usage

```
data(prematurity)
```

Format

An object of class `data.frame` with 189 rows and 11 columns.

Examples

```
data(prematurity)
```

Index

* **datasets**

prematurity, [4](#)

datach, [2](#)

pm3, [2](#)

pm3datalist, [3](#)

pm3fit, [4](#)

prematurity, [4](#)